SERIES FEATURES

- 120/277 VAC OPERATION
- 1.5 Hours of Emergency Illumination

₩

- INTEGRATED SOLID STATE SYSTEM
- CONSTANT CURRENT, CONTROLLED,
 AUTOMATIC CHARGER CIRCUIT
- Low Voltage Battery Cutoff
- ► BROWNOUT SENSITIVITY
- MAXIMUM INPUT RATING (120 OR 277 VAC)
 STANDARD 2.5 WATTS
 EMERGENCY LIGHT
- [2] 6 VDC, 4 WATT HIT LAMPS (PH)
 (TOTAL 8 WATTS)
- [2] 6 VDC, 4 WATT PAR-36 HIT LAMPS (TOTAL 8 WATT)
- LED (INDIRECT)

[1] STRIP, 120/277 VAC, 2.5 WATT

- ► LIGHT EMITTING DIODES 25+ YEAR LIFE
- ► ILLUMINATES WITH UNIFORM COLOR AND BRIGHTNESS
- ► INDIRECT PLACEMENT FOR DIFFUSED LEGEND OUTPUT
- ► Increased LED Brightness Level in Emergency Mode



- SEALED LEAD ACID BATTERY
- ▶ 6 Volt Operation (S65)
- ► MAINTENANCE FREE
- CEILING, END, OR BACK MOUNT
- CANOPY
- Universal Stencil
- DIRECTIONAL CHEVRON SNAPOUTS
 - 20 Gauge Steel Housing
 - POLYCARBONATE LAMP ENCLOSURES (-PH)
- ► WHITE POWDER COAT FINISH
- Easy Installation
- Amber (Power On) Indicator
- ► TEST SWITCH
- UL LISTED



COMBO-PH (RECTANGULAR HEADS)



COMBO (ROUND HEADS)

DIMENSIONS

HEIGHT: 13.0" WIDTH: 12.30" DEPTH: 2.3"

FACTORY OPTIONS

-DS DOUBLE LED STRIP-HI HIGH INTENSITY LED-U UNIVERSAL FACE



ORDERING INFORMATION

COMBO	2	R	W	W	U	-PH
Series	# Faces	LETTER COLOR	STENCIL COLOR	Housing Color	Options	HEAD TYPE
COMBO	1 2	<u>R</u> ed <u>G</u> reen	<u>W</u> HITE	<u>W</u> HITE	UNIVERSAL FACE ADDITIONAL BACKPLATE DOUBLE FACE ONLY U	

^{*} No Remote Capability