








SERIES FEATURES

	<ul style="list-style-type: none"> ▶ 120 VAC OPERATION STD. ▶ MAXIMUM INPUT RATING (120 OR 277 VAC) 20 WATTS
	<ul style="list-style-type: none"> ▶ ENERGY SAVING COMPACT FLUORESCENT ▶ [2] 120 VAC, 7 WATT LAMPS
	<ul style="list-style-type: none"> ▶ CEILING, END, OR BACK MOUNT ▶ CANOPY STANDARD ON DOUBLE FACE SIGN ▶ UNIVERSAL STENCIL ▶ DIRECTIONAL CHEVRON SNAPOUTS ▶ PRISMATIC DOWNLIGHT LENS ▶ DIE CAST ALUMINUM HOUSING ▶ MATTE BLACK FRAME ▶ BRUSHED ALUMINUM STENCIL FACE ▶ UL LISTED



ADDITIONAL EMERGENCY UNIT FEATURES

	<ul style="list-style-type: none"> ▶ INTEGRATED SOLID STATE SYSTEM ▶ CONSTANT CURRENT, AUTOMATIC CHARGER ▶ LOCK OUT (AUTOMATIC BATTERY CONNECT) ▶ LOW VOLTAGE BATTERY CUTOFF ▶ BROWNOUT SENSITIVITY ▶ MAXIMUM INPUT RATING (120 OR 277 VAC) 22 WATTS
	<ul style="list-style-type: none"> ▶ LONG LIFE INCANDESCENT ▶ [2] 6 VDC, 3 WATT LAMPS
	<ul style="list-style-type: none"> ▶ SEALED NICKEL CADMIUM BATTERY ▶ 6 VOLT OPERATION ▶ MAINTENANCE FREE
	<ul style="list-style-type: none"> ▶ CANOPY (WITH ELECTRONICS & BATTERY) ▶ TEST SWITCH ▶ RED (POWER ON) INDICATOR

FACTORY OPTIONS

-6	[2] 6 VDC, 6 WATT INCAN. LAMPS
-12	[2] 12 VDC, 6 WATT INCAN. LAMPS
-277	277 VAC INPUT
-2C	[2] INDEPENDENT AC CIRCUITS
-CPY	CANOPY
-HPF	HIGH POWER FACTOR
-OF	OPEN FACE (FIBER STD.)
-RMB	RECESSED MOUNT BLACK
-RMW	RECESSED MOUNT WHITE
-TP	TAMPER-PROOF SCREWS

DIMENSIONS

HEIGHT: 8.3"
WIDTH: 12.0"
DEPTH: 2.3"

AC CANOPY	EMER.
LENGTH: 4.7"	LENGTH: 9.0"
WIDTH: 4.7"	WIDTH: 4.7"
DEPTH: 0.8"	DEPTH: 2.3"



ORDERING INFORMATION

DX SERIES DX ~ DIE CAST	F LAMP TYPE F ~ FLUOR.	S POWER MODE A ~ AC S ~ EMERGENCY	2 # FACES 1 2	R LETTER COLOR R ED G REEN	A STENCIL COLOR W HITE B LACK A LUMINUM *	B HOUSING COLOR W HITE B LACK * A LUMINUM	-12 OPTIONS FACTORY OPTIONS
--------------------------------------	-------------------------------------	---	-------------------------------	--	--	--	--

* STANDARD



PHONE 815-459-7142 • FAX 815-459-6126

THE POWER TO PROTECT