



SERIES FEATURES

	<ul style="list-style-type: none"> ▶ 120 VAC OPERATION STD. ▶ MAXIMUM INPUT RATING 120 VAC 24 WATTS 277 VAC 30 WATTS
	<ul style="list-style-type: none"> ▶ LONG LIFE INCANDESCENT ▶ [2] 140 VAC, 15 WATT LAMPS
	<ul style="list-style-type: none"> ▶ CEILING, END, OR BACK MOUNT ▶ CANOPY STANDARD ON DOUBLE FACE SIGN ▶ UNIVERSAL STENCIL ▶ DIRECTIONAL CHEVRON SNAPOUTS ▶ PRISMATIC DOWNLIGHT LENS ▶ DIE CAST ALUMINUM HOUSING ▶ MATTE BLACK FRAME ▶ BRUSHED ALUMINUM STENCIL FACE ▶ UL LISTED

ADDITIONAL EMERGENCY UNIT FEATURES

	<ul style="list-style-type: none"> ▶ INTEGRATED SOLID STATE SYSTEM ▶ CONSTANT CURRENT, AUTOMATIC CHARGER ▶ LOCK OUT (AUTOMATIC BATTERY CONNECT) ▶ LOW VOLTAGE BATTERY CUTOFF ▶ BROWNOUT SENSITIVITY ▶ MAXIMUM INPUT RATING 120 VAC 26 WATTS 277 VAC 30 WATTS
	<ul style="list-style-type: none"> ▶ LONG LIFE INCANDESCENT ▶ [2] 6 VDC, 3 WATT LAMPS
	<ul style="list-style-type: none"> ▶ SEALED NICKEL CADMIUM BATTERY ▶ 6 VOLT OPERATION ▶ MAINTENANCE FREE
	<ul style="list-style-type: none"> ▶ CANOPY (WITH ELECTRONICS & BATTERY) ▶ TEST SWITCH ▶ RED (POWER ON) INDICATOR

FACTORY OPTIONS

- 6 [2] 6 VDC, 6 WATT INCAN. LAMPS
- 12 [2] 12 VDC, 6 WATT INCAN. LAMPS
- 277 277 VAC INPUT
- 2C [2] INDEPENDENT AC CIRCUITS
- CPY CANOPY (SGL FACE SIGNS)
- OF OPEN FACE (FIBER STD.)
- RMB RECESSED MOUNT BLACK
- RMW RECESSED MOUNT WHITE
- TP TAMPER-PROOF SCREWS

DIMENSIONS

HEIGHT: 8.3"	EMER. LENGTH: 9.0"
WIDTH: 12.0"	EMER. WIDTH: 4.7"
DEPTH: 2.3"	EMER. DEPTH: 2.3"
AC CANOPY LENGTH: 4.7"	
AC CANOPY WIDTH: 4.7"	
AC CANOPY DEPTH: 0.8"	



ORDERING INFORMATION

DX SERIES DX ~ DIE CAST	I LAMP TYPE I ~ INCAN.	S POWER MODE A ~ AC S ~ EMERGENCY	2 # FACES 1 2	R LETTER COLOR RED GREEN	A STENCIL COLOR WHITE BLACK ALUMINUM*	B HOUSING COLOR WHITE BLACK* ALUMINUM	-12 OPTIONS FACTORY OPTIONS
--------------------------------------	-------------------------------------	---	-------------------------------	--	--	--	---

* STANDARD

