
















SERIES FEATURES

-  ▶ 120 VAC OPERATION STD.
-  ▶ MAXIMUM INPUT RATING (120 OR 277 VAC) 20 WATTS
-  ▶ ENERGY SAVING COMPACT FLUORESCENT
-  ▶ [2] 120 VAC, 7 WATT LAMPS
-  ▶ ARCHITECTURAL GRADE
-  ▶ CLEAN, CONTEMPORARY STYLING
-  ▶ CEILING OR WALL MOUNT
-  ▶ RECESSED OR SURFACE HOUSING
-  ▶ ETCHED, CLEAR ACRYLIC, EDGE-LIT PANEL
-  ▶ SILK SCREENED LETTERS
-  ▶ STEEL HOUSING AND TRIM PLATE
-  ▶ WHITE POWDER COAT FINISH
-  ▶ UL LISTED

RECESSED SIGNS
ROUGH-IN
OPENING SIZE
5.65" x 14.85"
















- FACTORY OPTIONS**
- 277** 277 VAC INPUT (GXFA ONLY)
 - 2C** [2] INDEPENDENT AC CIRCUITS
 - PA** PLENUM CONSTRUCTION
 - E** END MOUNT

SPECIFY ARROW CONFIGURATION ON ALL EDGE LIT SIGNS:

BLANK = NO CHEVRON	
CR = CHEVRON RIGHT	>
CL = CHEVRON LEFT	<
CD = DUAL CHEVRON	<>
CRCL = CHEVRON RIGHT	① >
CHEVRON LEFT	< ②
(DOUBLE FACE ONLY)	



ADDITIONAL EMERGENCY UNIT FEATURES





-  ▶ DUAL VOLTAGE TRANSFORMER FOR 120/277 VAC OPERATION
-  ▶ INTEGRATED SOLID STATE SYSTEM
-  ▶ CONSTANT CURRENT, AUTOMATIC CHARGER
-  ▶ LOCK OUT (AUTOMATIC BATTERY CONNECT)
-  ▶ LOW VOLTAGE BATTERY CUTOFF
-  ▶ BROWNOUT SENSITIVITY
-  ▶ MAXIMUM INPUT RATING (120 OR 277 VAC) 24 WATTS
-  ▶ ENERGY SAVING XENON
-  ▶ [3] XENON (AC) & [4] HIT (DC) LAMPS
-  ▶ FULL LUMEN OUTPUT IN EMERGENCY MODE
-  ▶ SEALED NICKEL CADMIUM BATTERY
-  ▶ 10 YEAR BATTERY WARRANTY
-  ▶ MAINTENANCE FREE
-  ▶ TEST SWITCH
-  ▶ RED (POWER ON & CHARGE) INDICATOR

* STANDARD

ORDERING INFORMATION

GX SERIES GXFA ~ FLOUR. AC GXZS ~ XENON EMER.	1 # FACES 1 2	W TRIM COLOR W HITE * BR ASS M ATTE CHROME B LACK	R LETTER COLOR R ED G REEN W HITE	W † BKGRND. COLOR BLANK ~ NONE W ~ WHITE MB ~ MIRRORRED	C FITURE TYPE C EILING W ALL	R MOUNTING TYPE R ECESSED S URFACE	-277 OPTIONS FACTORY OPTIONS
---	-------------------------------	---	--	--	--	--	--

† STD. BACKGROUND COLOR OF SGL FACE SIGN IS CLEAR (BLANK). FOR NON-STD. SINGLE & ALL DOUBLE FACE SIGNS. INDICATE W FOR WHITE BACKGROUND OR MB FOR MIRRORRED BACKGROUND.



PHONE 815-459-7142 • FAX 815-459-6126

THE POWER TO PROTECT