


SERIES FEATURES

	▶ INTEGRATED SOLID STATE SYSTEM		
	▶ THREE-RATE, CONTROLLED, AUTOMATIC CHARGER		
	▶ LOW VOLTAGE BATTERY CUTOFF		
	▶ BROWNOUT SENSITIVITY		
	▶ FUSED AC INPUT & DC OUTPUT CIRCUIT PROTECTION		
	▶ SINGLE VOLTAGE TRANSFORMER FOR 120 VAC OPERATION		
	▶ MAXIMUM INPUT RATING 120VAC 60 Hz 0.50 AMPS 277VAC 60 Hz 0.23 AMPS		
	▶ PAR-46 SEALED BEAM LAMPS	S L T A M D P	▶ SEE UNIT INFORMATION
	▶ SEALED LEAD ACID BATTERY [S]		
	▶ REFILLABLE LEAD ACID BATTERY [L]		
	▶ 6 OR 12 VOLT OPERATION		
	▶ RUGGED 20 GAUGE STEEL HOUSING		
	▶ TOP END BATTERY ACCESS		
	▶ FULL LENGTH PIANO HINGE WITH LOCK HASP		
	▶ INTEGRAL CARRYING HANDLES		
	▶ TWO-TONE POWDER COAT FINISH (BEIGE & COCOA) STANDARD		
	▶ SLIDE OUT CONTROL CHASSIS		
	▶ TEST SWITCH		
	▶ BATTERY CAPACITY INDICATOR		
	▶ INCREMENTAL LED PANEL INDICATES CURRENT BATTERY CHARGE / DISCHARGE STATUS		
	▶ AMBER (AC ON) LED INDICATOR		
	▶ UL LISTED		

USE NO. 22 MOUNTING SHELF

UNIT INFORMATION

MODEL NUMBER	STD. LAMP WATT	WATTS PER HOUR								REPLACEMENT BATTERY
		1.5	2	3	4	5	6	7	8	
MS6L40 †	25	120	90	60	45	36	30	26	23	[1] L640
MS6S72 †	25	120	120	100	75	60	50	43	38	[2] S636
MS6S72DO †	25	200	150	100	75	60	50	43	38	[2] S636
MS6L100 †	25	120	120	120	120	96	80	69	60	[1] L6100
MS6L100DO †	25	225	169	145	120	96	80	69	60	[1] L6100
MS12S20 †	35	125	94	63	47	38	31	27	23	[1] S1220
MS12S36 †	35	200	150	100	75	60	50	43	38	[2] S636
MS12L60 †	35	240	180	120	90	72	60	51	45	[1] L1260
MS12S72 †	35	240	240	200	150	120	100	86	75	[4] S636
MS12S72DO †	35	400	300	200	150	120	100	86	75	[4] S636

† CHICAGO CODE APPROVED

ILLUMINATION IS RATED TO 87.5% OF NOMINAL SYSTEM VOLTAGE AND RECHARGE TO FULL CAPACITY WITHIN 24 HOURS.

NEC REQUIRES 1.5 HOURS OF EMERGENCY ILLUMINATION.

THE DO MODEL PROVIDES 2 SEPERATELY FUSED DC (20A) OUTPUT CIRCUITS FOR INCREASED SYSTEM CAPACITY, WITHOUT THE USE OF ADDITIONAL BATTERIES

SHOWN IN STANDARD
TWO TONE BEIGE &
COCOA FINISH



RUGGED STEEL CONSTRUCTION IS COMBINED WITH STATE-OF-THE-ART LED STATUS INDICATORS, MAKING THE MS SERIES AN IDEAL CHOICE FOR DEMANDING INDUSTRIAL APPLICATIONS. A SLIDE OUT MODULAR CONTROL ASSEMBLY ALLOWS FOR QUICK AND EASY PRODUCT UPGRADES.

DIMENSIONS

HEIGHT: 20.5"
WIDTH: 18.5"
DEPTH: 8.5"

FACTORY OPTIONS

- 277** 277 VAC INPUT
- BDS** BATTERY DISCONNECT SWITCH
- GY** GREY INDUSTRIAL FINISH
- CP** CORD & PLUG FOR 120 VAC INPUT
- QC** QUIK CHEK REMOTE TEST & TIME DELAY
- TD** TIME DELAY ADJUSTS 1-60 MIN.
- **** SPECIAL LAMP WATTAGE



SILTRON

PHONE 815-459-7142 • FAX 815-459-6126

THE POWER TO PROTECT