SERIES FEATURES

- HIGH FREQUENCY FLUORESCENT EFFICIENCY
- ► COMPATIBLE WITH MAGNETIC OR ELECTRONIC BALLASTS
- OPERATES 2' THROUGH 8' FLUORESCENT LAMPS
- OUT OF SIGHT EQUIPMENT LOCATION
- ► USABLE IN NEW CONSTRUCTION OR RETROFIT
- ▶ TEST SWITCH AND LED INDICATOR LIGHT INCLUDED
- ► NICKEL CADMIUM BATTERY
- Fully Automatic Brownout Sensing
- INSTALLATION DOES NOT AFFECT NORMAL OPERATION OF LAMP/BALLAST
- ALL STEEL POWDER COATED HOUSING
- SOLID STATE RELIABILITY
- SIMPLE INSTALLATION IN T-BAR TYPE CEILINGS.
- Low Voltage Disconnect
- MEETS OR EXCEEDS UL 924

LIGHT OUTPUT

| MP1800 | 1400 | 2 | 2 ' -4' |
|--------|------|---|----------------|
| MP1800 | 1400 | 1 | 2'-8' |

FITS MOST SINGLE AND BIPIN T8 & T12 LAMPS, HO OR VHO FLUORESCENT LAMPS.

NOTE: For Higher Lumens or More Lamps in Emergency Mode, Contact the Factory.



| DIMENSIONS |
|---|
| Ныднт. 3.5" Width: 23.75" Depth: 6" |
| |

FACTORY OPTIONS

-RTBH REMOTE MOUNTED TEST BUTTON AND PILOT LIGHT

ORDERING INFORMATION





MULTI-PAK SERIES