### **SERIES FEATURES**



- 120/277 VAC OPERATION
- MAXIMUM INPUT RATING (120 OR 277 VAC)

SINGLE FACE 3.6 WATTS
DOUBLE FACE 5.6 WATTS



- LIGHT EMITTING DIODES ~ 25+ YEAR LIFE
- ► ILLUMINATES WITH UNIFORM COLOR AND BRIGHTNESS
- ► 100-300 Ft. VISIBILITY
- Back, Ceiling, or End Mount
- CANOPY
- 20 Gauge Steel Housing
- ACRYLIC SHIELD
- WHITE POWDER COAT FINISH
- Universal Directional Chevrons
- ▶ UL LISTED



#### DIMENSIONS

HEIGHT: 7.5" WIDTH: 12.3" DEPTH: 2.0"

# Additional Emergency Unit Features

► MAXIMUM INPUT RATING (120 OR 277 VAC)

SINGLE FACE 6.8 WATTS
DOUBLE FACE 8.0 WATTS

₩

- INTEGRATED SOLID STATE SYSTEM
- CONSTANT CURRENT, CONTROLLED AUTOMATIC CHARGER CIRCUIT
- Low Voltage Battery Cutoff
- Voltage Surge Protection
- ► BROWNOUT SENSITIVITY



- SEALED NICKEL CADMIUM BATTERY
- ► 5 YEAR SHELF LIFE
- ▶ 10 YEAR BATTERY WARRANTY
- ► MAINTENANCE FREE



- 3+ Hours Illumination (Single Face) in DCMode
- 1.5+ Hours Illumination (Double Face) in DCMode
- ► TEST SWITCH
- AMBER (AC ON / CHARGER OPERATION) INDICATOR



## FACTORY OPTIONS

- -BZ BUZZER (EMER. ONLY)
- -DL DOWNLIGHT LED
- **-FAI** FIRE ALARM INTER-FACE. VISUAL ALARM
- -FL FLASHER (EMER. ONLY)
- -HI HIGH INTENSITY LED'S
- -REC RECESSED HOUSING
  - -TP TAMPER-PROOF SCREWS
  - -SL SLAVE

#### **ORDERING INFORMATION**

WXD Series	S Power Mode	2 # Faces	R LETTER COLOR	W STENCIL COLOR	W Housing Color	-FAI Options
WXD ~ STEEL	A ~ AC S ~ EMERGENCY	1 2	<u>R</u> ed <u>G</u> reen	<u>W</u> HITE * <u>B</u> LACK	<u>W</u> HITE * <u>B</u> LACK	Factory Options

27



<sup>\*</sup> STANDARD