



**SERIES FEATURES**

	▶ 120 VAC OPERATION STD.
	▶ MAXIMUM INPUT RATING (120 VAC) 24 WATTS (277 VAC) 30 WATTS
	▶ LONG LIFE INCANDESCENT [2] 140 VAC, 15 WATT LAMPS
	▶ CEILING, END, OR BACK MOUNT
	▶ CANOPY
	▶ UNIVERSAL STENCIL
	▶ DIRECTIONAL CHEVRON SNAPOUTS
	▶ DOWNLIGHT
	▶ 20 GAUGE STEEL HOUSING
	▶ WHITE POWDER COAT FINISH
▶ UL LISTED	

**ADDITIONAL EMERGENCY UNIT FEATURES**

	▶ INTEGRATED SOLID STATE SYSTEM
	▶ MULTI-RATE, CONTROLLED AUTOMATIC CHARGER
	▶ LOCK OUT (AUTOMATIC BATTERY CONNECT)
	▶ LOW VOLTAGE BATTERY CUTOFF
	▶ BROWNOUT SENSITIVITY
	▶ DUAL VOLTAGE TRANSFORMER FOR 120/277 VAC OPERATION
	▶ MAXIMUM INPUT RATING: (120 OR 277 VAC) 26 WATTS
	▶ LONG LIFE INCANDESCENT [2] 6 VDC, 6 WATT LAMPS
	▶ SEALED LEAD ACID BATTERY
	▶ 6 VOLT OPERATION ▶ MAINTENANCE FREE
	▶ TEST SWITCH
	▶ RED (POWER ON) LED INDICATOR

**FACTORY OPTIONS**

- 6 [2] 6 VDC, 6 WATT INCAN. LAMPS
- 12 [2] 12 VDC, 6 WATT INCAN. LAMPS
- 277 277 VAC INPUT (WXIA)
- 2C [2] INDEPENDENT AC CIRCUITS
- OF OPEN FACE PANEL (FIBER STD.)
- U UNIVERSAL FACE ADD'L BACKPLATE DBL FACE ONLY
- REC RECESSED HOUSING (WXIA)
- TP TAMPER-PROOF SCREWS

**DIMENSIONS**

HEIGHT: 7.5"	LENGTH 10.5"
WIDTH: 12.3"	WIDTH 12.3"
DEPTH: 2.0"	HEIGHT 2.0"



**ORDERING INFORMATION**

<b>WX</b> SERIES WX ~ STEEL	<b>I</b> LAMP TYPE I ~ INCAN.	<b>S</b> POWER MODE A ~ AC S ~ EMERGENCY	<b>2</b> # FACES 1 2	<b>R</b> LETTER COLOR R ED G REEN	<b>W</b> STENCIL COLOR W HITE* B LACK	<b>W</b> HOUSING COLOR W HITE* B LACK	<b>-U</b> OPTIONS FACTORY OPTIONS
-----------------------------------	-------------------------------------	---	-------------------------------	--	--	--	---

\* STANDARD

