



**DIMENSIONS**

HEIGHT: 9.5"      HEIGHT: 12.5"  
 WIDTH: 12.3"     WIDTH: 12.3"  
 DEPTH: 2.0"      DEPTH: 2.0"

**FACTORY OPTIONS**

- 6** [2] 6 VDC, 6 WATT INCAN. LAMPS
- 12** [2] 12 VDC, 6 WATT INCAN. LAMPS
- 277** 277 VAC INPUT
- 2C** [2] INDEPENDENT AC CIRCUITS
- U** UNIVERSAL FACE ADD'L BACKPLATE DBL FACE ONLY
- SM** SIDE MOUND BATTERY PACK
- TP** TAMPER-PROOD SCREWS

**SERIES FEATURES**

	<ul style="list-style-type: none"> <li>▶ 120 VAC OPERATION STD.</li> <li>▶ MAXIMUM INPUT RATING 120 VAC 24 WATTS 277 VAC 30 WATTS</li> </ul>
	<ul style="list-style-type: none"> <li>▶ LONG LIFE INCANDESCENT</li> <li>▶ [2] 140 VAC, 15 WATT LAMPS</li> </ul>
	<ul style="list-style-type: none"> <li>▶ OPEN FACE GLASS PANEL</li> <li>▶ SILK SCREEN LETTERS</li> <li>▶ CEILING, END, OR BACK MOUNT</li> <li>▶ CANOPY</li> <li>▶ DOWNLIGHT</li> <li>▶ 20 GAUGE STEEL HOUSING</li> <li>▶ WHITE POWDER COAT FINISH</li> <li>▶ UL LISTED</li> <li>▶ CHICAGO CODE APPROVED</li> </ul>

**ADDITIONAL EMERGENCY UNIT FEATURES**

	<ul style="list-style-type: none"> <li>▶ INTEGRATED SOLID STATE SYSTEM</li> <li>▶ MULTI-RATE, CONTROLLED, AUTOMATIC CHARGER ~</li> <li>▶ LOCK OUT (AUTOMATIC BATTERY CONNECT)</li> <li>▶ LOW VOLTAGE BATTERY CUTOFF</li> <li>▶ BROWNOUT SENSITIVITY</li> <li>▶ DUAL VOLTAGE TRANSFORMER FOR 120/277 VAC OPERATION</li> <li>▶ MAXIMUM INPUT RATING (120 OR 277 VAC) 26 WATTS</li> </ul>
	<ul style="list-style-type: none"> <li>▶ LONG LIFE INCANDESCENT</li> <li>▶ [2] 6 VDC, 6 WATT LAMPS</li> </ul>
	<ul style="list-style-type: none"> <li>▶ SEALED LEAD ACID BATTERY</li> <li>▶ 6 VOLT OPERATION</li> <li>▶ MAINTENANCE FREE</li> </ul>
	<ul style="list-style-type: none"> <li>▶ TEST SWITCH</li> <li>▶ RED (POWER ON) LED INDICATOR</li> </ul>

\* MUST SPECIFY ARROW DESIGNATION



**ORDERING INFORMATION**

<b>WX</b> SERIES WX ~ STEEL	<b>I</b> LAMP TYPE I ~ INCAN.	<b>S</b> POWER MODE A ~ AC S ~ EMERGENCY	<b>2</b> # FACES 1 2	<b>R</b> LETTER COLOR RED GREEN	<b>W</b> STENCIL COLOR WHITE * BLACK	<b>W</b> HOUSING COLOR WHITE * BLACK	<b>-U</b> OPTIONS FACTORY OPTIONS	<b>-CH</b>
-----------------------------------	-------------------------------------	---	-------------------------------	--	---	---	--	------------

\* STANDARD



PHONE 815-459-7142 • FAX 815-459-6126

THE POWER TO PROTECT