

DIMENSIONS

HEIGHT: 7.5" WIDTH: 12.3" DEPTH: 2.0"

FACTORY OPTIONS

- -6 [2] 6 VDC, 6 WATT INCAN. LAMPS
- **-12** [2] 12 VDC, 6 WATT INCAN. LAMPS
- -DS DOUBLE LED STRIPS FOR INCREASED **ILLUMINATION LEVEL** OR 2CKT **OPERATION**
- -HI HIGH INTENSITY LED'S
- -U UNIVERSAL FACE ADD'L BACKPLATE **DBL FACE ONLY**
- -DMP DAMP LOCATION
- -REC RECESSED HOUSING
 - -TP TAMPER-PROOF **S**CREWS

SERIES FEATURES

- 120/277 VAC OPERATION
- MAXIMUM INPUT RATING (120 OR 277 VAC) 1.7 WATTS STANDARD DS OPTION 3.5 WATTS



- LIGHT EMITTING DIODES ~ 25+ YEAR LIFE
- ILLUMINATES WITH UNIFORM COLOR AND BRIGHTNESS
- INDIRECT PLACEMENT FOR DIFFUSED LEGEND OUTPUT
- CEILING, END, OR BACK MOUNT
- CANOPY
- UNIVERSAL STENCIL
- DIRECTIONAL CHEVRON SNAPOUTS
- 20 Gauge Steel Housing
- WHITE POWDER COAT FINISH
- Easy Installation
- UL LISTED

Additional Emergency Unit Features



- INTEGRATED SOLID STATE SYSTEM
- CONSTANT CURRENT. CONTROLLED **AUTOMATIC CHARGER CIRCUIT**
- Low Voltage Battery Cutoff
- BROWNOUT SENSITIVITY



- INCREASED LED BRIGHTNESS LEVEL IN EMERGENCY MODE
- SEALED NICKEL CADMIUM BATTERY
- 5 YEAR SHELF LIFE
- 10 YEAR BATTERY WARRANTY
- Maintenance Free



- 3+ Hours Illumination in Emergency Mode**
- TEST SWITCH
- LED (Power On) Indicator

^{**} Longer illumination times available. Consult factory.





ORDERING INFORMATION

ı	WXL	S	2	R	W	W	-DS
	SERIES	Power Mode	# FACES	LETTER COLOR	STENCIL COLOR	Housing Color	OPTIONS
	WXL ~ STEEL	A ~ AC S ~ EMERGENCY	1 2	<u>R</u> ed <u>G</u> reen	<u>W</u> HITE * <u>B</u> LACK	<u>W</u> HITE * <u>B</u> LACK	Factory Options

* STANDARD

PHONE 815-459-7142 • FAX 815-459-6126 THE POWER TO PROTECT